



Product Data Sheet

JetMax™ JM 9020 Gloss Paper

- ❖ **64 lb. Gloss Inkjet Paper**
- ❖ **All Temperature Acrylic Adhesive**
- ❖ **40 lb. CK Liner**
- ❖ **Total Construction Caliper: .007"**

Typical Applications and Uses: The permanent adhesive provides excellent performance and ultimate adhesion to all industrial drum types including steel, fiber and HDPE. The 64 lb. gloss paper face sheet has been optimized to provide excellent print quality and quick drying when using Epson® DURABrite® and NeuraLabel® pigment inkjet inks.

As with all pressure sensitive and non-pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

Performance Characteristics

Face: 64 lb. gloss inkjet paper

Liner: 40 lb. CK liner. Can be used for roll to roll or fan-fold.

Adhesive: All temperature acrylic adhesive.

- ❖ **Service Temperature Range:** -65°F to +200°F
- ❖ **Minimum Application Temperature:** -20°F

Adhesion to Stainless Steel: 1.2 lbs./in.

Versatility: Excellent through Epson® ColorWorks® and NeuraLabel® inkjet printers.

Topcoat: Gloss surface provides excellent print quality when using pigment inkjet inks.

Printability: Exterior light-fast inks available upon request.

Converting: Can be die cut and stripped.

Storage Suitability: 1 year when stored at 70°F and 50% RH.