



## Product Data Sheet

### JetMax™ JM 9025 High Gloss Paper

- ❖ 60 lb. High Gloss Inkjet Paper
- ❖ All Temp Acrylic Adhesive
- ❖ 40 lb. SCK Liner
- ❖ Total Construction Caliper: .0073"

---

**Typical Applications and Uses:** The all temperature adhesive provides excellent performance and adhesion to all industrial drum types including steel, fiber and HDPE. The 60 lb. high gloss paper face sheet has been optimized to provide excellent print quality and quick drying when using water-based and pigment inkjet ink technology.

As with all pressure sensitive and non-pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

---

#### Performance Characteristics

**Face:** 60 lb. High Gloss Paper.

**Liner:** 40 lb. liner designed for roll products.

**Adhesive:** All-temperature emulsion acrylic adhesive with excellent initial tack primarily for industrial applications.

- ❖ **Service Temperature Range:** -30°F to +200°F
- ❖ **Minimum Application Temperature:** -20° F

**Adhesion to Stainless Steel:** 1.42 lbs./in.

**Topcoat:** Specially designed topcoat optimized for on demand inkjet printing.

**Printability:** Accepts spot color flexo inks.

**Converting:** Can be die cut and stripped.

**Storage Suitability:** 1 year when stored at 70°F and 50% RH.