



## Product Data Sheet

### JetMax™ JM 9080 Gloss White Polyester

- ❖ 3.1 mil Gloss White Inkjet Top Coated Polyester
- ❖ Permanent Acrylic Pressure Sensitive Adhesive
- ❖ 40 lb. Super Calendered Kraft (SCK) Liner
- ❖ Total Construction Caliper - .0077"

---

**Typical Applications and Uses:** The permanent acrylic adhesive provides excellent performance and ultimate adhesion to all industrial drum types including steel, fiber and HDPE. The 3.1 mil Gloss White Polyester face sheet has excellent dimensional stability and good weather resistance. Excellent photo-realistic imaging. It has been optimized to provide superior print quality and quick drying when using Epson® DURABrite® and NeuraLabel® pigment inkjet inks.

As with all pressure sensitive and non-pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

---

#### Performance Characteristics

**Face:** 3.1 mil gloss white ink jet top coated polyester provides superior Inkjet printability.

**Liner:** 40lb. SCK economical liner. Can be used for roll to roll and some fanfold designs.

**Adhesive:** Permanent acrylic adhesive with excellent initial tack primarily for industrial applications.

- ❖ **Service Temperature Range:** -20°F to +212°F
- ❖ **Minimum Application Temperature:** +23°F

**Tack:** 12.5 N

**Versatility:** Excellent through Epson® ColorWorks® and NeuraLabel® inkjet printers.

**Topcoat:** Gloss surface provides excellent print quality when using pigment inkjet inks.

**Chemical Resistance:** Marginal image chemical resistance. Applied labels including inkjet image are resistant to water, mild acids, salts, and some petroleum-based oils.

**Converting:** Can be die cut and stripped.

**Storage Suitability:** 1 year when stored at 70°F and 50% RH.