



Product Data Sheet

LaserPlus™ LP 1850 Semi-Gloss Paper

- ❖ **54 lb. Semi-Gloss Paper Face – .0026” caliper +/- 10%**
- ❖ **Permanent Acrylic Pressure Sensitive Adhesive**
- ❖ **53 lb. Lay Flat Liner - .00323” caliper +/- 10%**
- ❖ **Total Construction Caliper - .00663**

Typical Applications and Uses: Semi-Gloss face stock that provides sufficient opacity and strength for many label applications and provides excellent toner anchorage in many printers. Typical applications include inventory labels, order picking & instruction, office use and price stickers. The permanent adhesive is designed for excellent adhesion to corrugated cardboard and superior adhesion to plastics.

As with all pressure sensitive and non-pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

Performance Characteristics

Face: 54 lb. Semi-Gloss Laser paper provides excellent laser toner printability in many printers.

Liner: 53lb. LF liner for roll to roll, roll to fanfold, and roll to sheet applications.

Adhesive: Permanent acrylic adhesive with excellent initial tack for many applications.

- ❖ **Service Temperature Range:** -65°F to +200°F
- ❖ **Minimum Application Temperature:** +38°F

Adhesion to Recycled Corrugated: 9.6 – 12.8 oz/in.

Versatility: Excellent through toner laser printers. Testing is suggested.

Printability: Flexo pre-printing available including exterior light-fast inks upon request.

Converting: Can be die cut and stripped.

Storage Suitability: 1 year when stored at 70°F and 50%RH.