

Facestock

Transparent PP film specifically top coated to receive dye and pigment-based ink-jet inks. Capable of printing photo-realistic images that are resistant to water and other semi-harsh chemicals.

Basis Weight:	53# per ream (25" x 38") TAPPI-410
Caliper:	3.1mil TAPPI-411
Tensile Strength MD:	77lb/in TAPPI-494
Tensile Strength CD:	36lb/in TAPPI-494
Transparency:	92% ISO 2471

Adhesive

Designed specifically for applications requiring good initial tack and ultimate adhesion as well as good heat resistance. In combination with a clear face and a PET liner offers excellent clarity and wet out for "no label look".

Type:	Permanent
Composition:	Waterborne Acrylic
Tack:	11 N FTM9
PE-Looptack:	9 N modified FTM9
Service Temperature Range:	-20° F to 212° F subject to facestock limitations
Minimum Labelling Temperature:	23° F

Limitations: Limited adhesion at low temperatures. The highest end-use temperature must be separately checked together with the face material.

Backing

White, one-side coated kraft liner for roll-to-roll labeling applications.

Substance Weight:	52# per ream (24" x 36") TAPPI-410
Caliper:	3.2mil TAPPI-411

Shelf Life

From the date of manufacture, two years when stored at 68°F at 50% RH.

Performance

Total Construction Caliper (approximate):	6.9 mil ± 10
Substance Weight:	122 lbs. per ream (25" x 38")

Disclaimer: The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All of our products are sold subject to Trebnick System's general sales conditions, and you should ensure that any existing laws are observed

This publication replaces all previous versions. All information is subject to change without notice.