

Facestock

A matte white Ink polypropylene film material that is designed for harsh environments. Featuring excellent water resistance along with instant-dry coating. Stock #2260 is inkjet printable with water-based inks and is excellent for HDPE drum labeling.

Basis Weight lbs/ream: 25x38-500	39 +/- 10%
Caliper - mils	3.4 +/- 10%
Tensile - lbs/in (MD/CD)	- / -
Opacity	87%
Brightness	90%

Adhesive

A high tack, emulsion acrylic, permanent adhesive that is specifically designed for labeling all types of chemical drum substrates and other rough surfaces. When used with certain film face stocks, it has passed BS5609 testing standards.

Tack (N)	8
PE-Looptack (N)	16
Minimum Application Temperature	10°F -12°C
Service Temperature*	-20°F - 220°F
*Subject to facestock limitations	-29°C - 104°C

Backing

A bleached, one-side coated kraft stock featuring high internal strength, toughness, and tear resistance. Ideally suited for marginal punching, perforating, and fanfolding.

Basis Weight lbs/ream: 24x36-500	53 +/- 10%
Caliper - mils	3.2 +/- 10%
Tensile - lbs/in (MD/CD)	53 / 19
Opacity	-
Brightness	84%

Shelf Life

One year from the date of manufacture. To maximize product longevity, we recommend storage at 72°F at 50% RH. avoiding direct sunlight.

Performance

Total Construction Caliper (approximate):	7.6 mil +/- 10%
Substance Weight lbs/ream: 25 x 38-500	116 +/- 10%

Disclaimer: The performance of the product should always be tested in the actual application conditions. Our recommendations are based on our most current knowledge and experience. As our products are used in conditions beyond our control, we cannot assume any liability for damage caused through their use. Users of our products are solely responsible that the product is suitable for its intended application, and have determined such at their sole discretion. Users must comply with any applicable legislation and/or testing requirements for the finished article, and are responsible for bringing their products to market.

This publication does not constitute any warranty, express or implied, and is intended only for the recipient and cannot therefore be transferred to any third party. We cannot assume any liability for the use of our products in conjunction with other materials.

All of our products are sold subject to Trebnick System's general sales conditions, and you should ensure that any existing laws are observed.

This publication replaces all previous versions. All information is subject to change without notice.